

SARCUT L 22 is a medium viscosity high performance chlorine and sulphur free neat cutting oil formulated with advanced lubricity additives together with an anti-mist agent to improve operator and machine shop conditions.

Manufactured from selected solvent refined base stocks this product is formulated to be very economical in use and therefore is suitable to replace recycled or regenerated neat cutting oils that are often based on poor quality materials. Operators can benefit from improvements in health and safety with reduced risk of coming into contact with low quality unrefined oils from unknown origins.

APPLICATION

Use as received for applications requiring a low viscosity oil. Formulated with lubricity esters to give outstanding performance on operations requiring no sulphur or chlorine in the formulation, i.e. for use on yellow metals.

BENEFITS

- Low viscosity ensures good flushing of machine debris
- Suitable for a variety of machining operations on yellow metals and sensitive aluminium alloys
- Suitable for light to medium severity tapping, general machining and drilling operations

TYPICAL PROPERTIES

Appearance:	Pale Amber Oil
Specific Gravity @ 15.6°C:	0.89 – 0.90
Kinematic Viscosity @ 40°C:	20 - 24 cSt
Chlorine:	No
Sulphur:	No
Ester:	Yes

HEALTH & SAFETY, STORAGE AND DISPOSAL

SARCUT L 22 has been manufactured to the highest standards and is unlikely to present any significant health or safety hazard when used as recommended by SAR Lubricants. Good standards of personal and industrial hygiene are to be maintained by the user (see Material Safety Data Sheets). In order to protect the environment, the product used should be safely disposed of by a licensed contractor. The packaging material should be handled by a recognised reconditioning firm.

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT.

SAR Lubricants assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of SAR Lubricants