

**SARCUT NSF 22** is a neat oil blended from fully solvent refined mineral oil and a carefully balanced additive system.

## APPLICATION

To be used as received for honing, broaching, grinding, gear cutting and general machining operations where a light viscosity oil with excellent lubricity would be considered appropriate. Suitable for use with high-alloyed steels and non-ferrous metals, and formulated to protect against staining of yellow metals.

## BENEFITS

- Good cooling properties.
- Enhanced lubricity promotes excellent metal wetting and improves surface finish of machined parts.
- Low viscosity ensures good flushing of machined debris.
- Retention of viscosity ensures good penetration and settling of swarf.
- Lightly chlorinated.

## TYPICAL PROPERTIES

Appearance:	Amber Fluid
Viscosity @ 400C:	20 cSt
Specific Gravity @ 15.60C:	0.870 – 0.890
Chlorine:	Yes
Ester:	Yes
Sulphur:	No

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.