

Last Updated: 21.11.2017

Product Code: MW0570

**SARDRAW 46** is a high quality forming and drawing oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

(Product formerly known as SARFORM 46)

## **APPLICATION**

Designed for forming, drawing and rolling applications when working with ferrous components. The modern, high performance, ashless EP package also makes this product suitable for many other general machining operations. Application is usually by brush, roller or spray.

Note – not suitable for use with yellow metals as staining may occur.

## **BENEFITS**

- Versatile formulation makes this suitable as a multi-purpose product for machining all types of ferrous metals.
- Enhanced lubricity.
- Low oil mist levels.
- High performance EP package helps promote extended tool life.

## **TYPICAL PROPERTIES**

Appearance:	Amber fluid
Specific Gravity @ 15.6°C:	0.900
Kinematic Viscosity @ 40°C:	41.4-50.6 cSt
Sulphur:	Yes
Chlorine:	Yes
Ester:	Yes

## **HEALTH & SAFETY**

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.