

**SARFORM 37** is a high quality mould release oil formulated using solvent-refined mineral oil, together with hydrocarbon solvent elements and a purpose-designed additive package.

## APPLICATION

Developed as a low viscosity product ideal for use in the production of fired clay, tile, brick and concrete products, especially where a very high quality surface finish is desirable.

Application may be by either brush, roller or spray, (use appropriate respiratory protection if spraying). For best results, avoid excessive build-up of product, especially in tight angles.

For ease of application, **Sarform 37** is supplied ready for use and requires no additional mixing or stirring before utilisation.

## BENEFITS

- Designed to reduce the risk of surface blemishes, blowholes and staining on finished products.
- Operator-friendly formulation with low/reduced odour.
- Suitable for use with all types of plastic or steel moulds and shuttering.
- Low viscosity formulation promotes ease of coverage over the mould surfaces.
- Formulated with the incorporation of effective rust inhibiting properties.

## TYPICAL PROPERTIES

|                          |                   |
|--------------------------|-------------------|
| Appearance:              | Pale amber liquid |
| Specific Gravity @ 15°C: | 0.839             |
| Viscosity @ 40°C:        | 3.7 cSt           |
| Flash Point °C:          | 81                |

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.