

SARSOL MOULD OIL 4 : 1 is a high performance, soluble mould release agent.

APPLICATIONS

For optimum performance, a 20% solution (4 parts water to 1 part oil) is recommended. Application may be either by brush, roller or spray (use appropriate respiratory protection when spraying). Avoid excessive build-up of product, especially in tight angles.

Water hardness should be checked to determine optimum running concentrations - consult your SAR Lubricants Sales Engineer for further details.

FEATURES/BENEFITS

- High oil content.
- Excellent separation properties.
- Promotes good surface finish.
- Economical in use.
- Excellent anti-corrosion properties when used as recommended.

TYPICAL PROPERTIES

Appearance	Forms a white milky emulsion
Specific Gravity @ 15.6°C	0.90
pH (3% solution)	8.9

STORAGE

SARSOL MOULD OIL 4 : 1 should be stored in dry conditions and protected from extreme temperatures: 4-35°C is the recommended storage temperature.

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.