

Last Updated: 19.02.2014

Product Code: IP0392

SARTEC 40 is a medium to long term rust preventative, which leaves a thin protective film giving excellent indoor storage protection, lasting up to twelve months. Will give covered outdoor protection of 6 months and uncovered for 3 months.

APPLICATION

Use as received and apply by spray, brush or dipping in a well ventilated area. Leaves a waxy film on drying.

BENEFITS

- Safe on ferrous and non-ferrous metals
- Provides medium to long term protection of metal components when stored undercover
- Easily removed with petroleum spirit or other hydrocarbon solvents
- Good corrosion protection
- Excellent penetration
- Non staining
- Ideal as a protection for agricultural machinery, metal stocks etc.

TYPICAL PROPERTIES

Appearance:	Fluid Oil	Specific Gravity @ 15.6°C:	0.8414
Colour:	Brown	Indoor Protection:	6-12 Months
Flash Point:	64°C	Kinematic Viscosity @ 40°C:	10.0 cSt

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.