

Last Updated: 02.03.2009

Product Code: IP 0394

**SARTEC 505** is a high quality solvent deposited rust preventive with excellent dewatering properties.

## APPLICATION

Use as received and apply by brush, dip or spray for outstanding corrosion protection and water displacement. The protective film can be removed by using aqueous or solvent based cleaners.

## BENEFITS

- Excellent dewatering properties
- Leaves a thin oily protective film
- Good corrosion protection
- Lanolin free
- Fast drying hydrocarbon solvent
- Suitable for components exposed to salt spray

## TYPICAL PROPERTIES

Appearance:	Light brown fluid
Characteristics:	Non-drying oily film
Indoor Protection:	6-12 months
Density @ 15°C:	0.815
Humidity Cabinet Test:	Pass < 30 days
Flash Point:	40°C

BS Type 2B

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

### **SAR LUBRICANTS (SQUIRE A. RADCLIFFE & SONS LTD)**

Gill Bridge Oil Works, Lowlands Road, MIRFIELD,  
West Yorkshire, WF14 8LU | Tel: +44 (0)1924 494371  
Fax: +44 (0)1924 498940 | Email: enquiries@sarlubricants.co.uk

Registered In England: 05866783 VAT Registration No: 889171963



Certificate Number  
12669  
ISO 9001