

Last Updated: 02.03.2009

Product Code: IP 0393

SARTEC 606 is an oily corrosion preventive suitable for ferrous and non-ferrous materials giving outstanding protection for up to 12 months.

APPLICATION

Use as received and apply by brush, dip or spray, although its dewatering action is most effective if the articles to be protected can be immersed in a dip tank. The protective film can be removed by using aqueous or solvent based chemicals.

BENEFITS

- Excellent dewatering properties
- Good corrosion protection
- High resistance to emulsification
- Lanolin free
- Fast drying hydrocarbon solvent
- Leaves a thin oily protective film, offering protection up to 12 months
- Exceptional water separation promotes easy removal of settled water from the tank

TYPICAL PROPERTIES

Appearance:	Light brown fluid
Flash Point:	40°C
BS Type:	2B
Specific Gravity:	0.824
Humidity Cabinet Test:	Pass <30 days
Indoor Protection:	6-12 months

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.