

**STEAM CYLINDER OILS 1000 and 680** are heavy viscosity compounded oils for use in most types of stationary engines and steam engine cylinders.

## APPLICATION

Suitable for the lubrication of stationary engines and steam engine cylinders, especially when working in the presence of superheated or saturated steam.

## BENEFITS

- Exceptional film strength and thermal stability together with excellent lubricating and load-bearing capabilities.
- Provides corrosion protection, especially during long periods of downtime.
- Enhances free piston movement on initial start-up.
- Suitable for operations involving superheated, wet or dry steam conditions.

## TYPICAL PROPERTIES

	<u>ISO 1000</u>	<u>ISO 680</u>
Colour:	Dark amber fluid	Dark amber fluid
Kinematic Viscosity @ 40°C (ISO 3104) cSt:	900-1100	612-748
Flash Point (ISO 2592) °C:	315	255
Density @ 15°C (ASTM D1298) kg/l:	0.931	0.905

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.