

Last Updated: 31.07.2017

Product Code: GR0781

SUPER MOLY 5 is a premium quality multi-purpose grease for use in all anti-friction bearings subjected to high load conditions. The incorporation of an enhanced molybdenum disulphide content imparts a very high degree of wear protection against load, shock loading and dusty environments. Suitable for use in applications throughout industry and the automotive sector.

APPLICATION

Super Moly 5 can be applied manually or by using a standard grease gun (400gm cartridges available), or via a central lubricating system capable of pumping an NLGI No.2 grease. As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

BENEFITS

- Exceptional extreme pressure and anti-wear additives
- High degree of corrosion protection
- Enhanced adhesive properties to prolong performance profile and product life
- Highly versatile multi-purpose grease

TYPICAL PROPERTIES

Appearance:	Smooth Grease	Copper Corrosion (IP 112):	Pass
Colour:	Grey / Black	Resistance To Corrosion Emcor (IP 220):	0 : 0
NLGI Classification:	2	Water Washout (ASTM D1264) @ 39°C %:	3
Thickener:	Lithium Soap	Four Ball Weld Load (IP 239) kgs:	450
Base Oil:	Mineral Oil	Timken OK Load (IP 326) lbs:	50
Base Oil Viscosity @ 40°C (IP 71) cSt:	180	Oxidation Stability @ 100°C (IP 142)	
Worked Penetration (IP 50):	265 to 295	Pressure Drop After 100 hrs psi:	4
Dropping Point (IP 132) °C:	185 min.	Molybdenum Disulphide Content %:	5
Oil Separation (IP 121) %:	5 max.	Operating Temperature Range:	-20°C to +140°C

HEALTH AND SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.