

Last Updated: 22.06.2016  
Product Codes: IP0515/IP0520/IP0530

**SUPERTEC 15, 20 & 30** are medium to long term rust preventatives which leave a thin protective film giving excellent indoor storage protection for up to 2 years, depending on the grade. They also offer extensive protection for components stored outdoors, both covered and uncovered – please see table below for further details.

## APPLICATION

Use as received - apply by spray, brush or dipping in a well-ventilated area. Leaves a thin waxy film on drying.

## BENEFITS

- Each grade contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Outstanding corrosion protection properties.
- Excellent penetration qualities.
- Non-staining formulations.
- Provide medium to long term protection of metal components when stored undercover.
- Ideal for protection of metal stocks, agricultural machinery etc.

## TYPICAL PROPERTIES

	<u>SUPERTEC 15</u>	<u>SUPERTEC 20</u>	<u>SUPERTEC 30</u>
Appearance:	Amber fluid	Amber fluid	Amber fluid
Specific gravity @15°C	0.809	0.810	0.820
Flash Point (COC):	38°C	38°C	38°C
Non-volatile residue:	17%	22%	36%
Film thickness:	20 microns	26 microns	46 microns
Indoor protection:	>6 months	>6 months	>2 years
Outdoor protection:	>1 month	>1 month	>1 year

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.