

Last Updated: 20.05.2014
Product Codes: IP0520/IP0530

SUPERTEC 217 is a medium term rust preventative which leaves a thin protective film giving excellent indoor storage protection for up to 6 months. It also offers protection for components stored outdoors, both covered and uncovered – please see table below for further details.

APPLICATION

Use as received - apply by spray, brush or dipping in a well-ventilated area. Leaves a thin waxy film on drying.

BENEFITS

- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Outstanding corrosion protection properties.
- Excellent penetration qualities.
- Non-staining formulation.
- Provides medium term protection of metal components when stored undercover.
- Ideal for protection of metal stocks, agricultural machinery etc.

TYPICAL PROPERTIES

Appearance:	Amber fluid
Specific gravity @15°C	0.810
Flash Point (COC):	38°C
Non-volatile residue:	22%
Film thickness:	26 microns
Indoor protection:	>6 months
Outdoor protection:	>1 month

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.