

SUPERTEC PLUS 26 is high quality rust preventative capable of offering excellent indoor storage protection of over 2 years. Formulated with a high flashpoint capability, making it suitable for application where components exhibit a high surface temperature.

APPLICATION

Use as received - apply by spray, brush or dipping in a well-ventilated area. Leaves a soft waxy film on drying, which is easily removed by normal solvent degreasing processes.

BENEFITS

- High flashpoint capability makes it suitable for use where components to be treated have a high surface temperature.
- Contains a highly-efficient dewatering agent to quickly and effectively remove moisture from treated metal surfaces.
- Compatible with both ferrous and non-ferrous metals.
- Outstanding corrosion protection properties.
- Excellent penetration qualities.
- Non-staining formulation.
- Provides exceptional long term protection of metal components when stored undercover.
- Ideal for long term protection of all metal stocks, agricultural machinery etc.

TYPICAL PROPERTIES

Appearance:	Amber/Brown fluid
Specific gravity @15°C	0.8936
Flash Point (COC) :	>150°C
Indoor protection:	>2 years
Outdoor protection:	<2 years

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.