

Last Updated: 05.08.2009

Product Code: SFV 0032; SFV 0046; SFV 0068; SFV 0100

**SARFOOD VHVI HYDRAULIC OILS** are food grade, non-toxic developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

## APPLICATION

Sarfood VHVI Hydraulic Oils are suitable for hydraulic systems designed to operate in applications where ISO 32, 46, 68 and 100 oil viscosity grades are used. Follow manufacturer's instructions. It is important to purge the system of the previous oil prior to recharging with Sarfood VHVI Hydraulic Oils.

## BENEFITS

- Low coefficient of friction provides excellent lubrication and reduces wear
- Fully synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals
- Low foaming reduces residue and scum build-up, which extends maintenance intervals

## TYPICAL PROPERTIES

ISO 32, 46, 68 & 100

Appearance:	Clear Fluid
Base Fluid:	Blend of Synthetic Oils
Temperature Range:	- 15°C to + 150°C

## HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.